



Specification Data -- RESILIENT TILE FLOORING 09 65 19

Burke Flooring Adhesives And LEED NC 2.2 EQ Credit 4.1 for Low Emitting Materials

In response to typical questions about Burke Flooring's Adhesives and LEED EQ Credit 4.1: Low-Emitting Materials: Adhesives & Sealants, we are providing the following compliance information:

LEED-NC 2.2 - Indoor Environmental Quality

EQ Credit 4.1: Low-Emitting Materials: Adhesives & Sealants

EQ Credit 4.1 stipulates that all adhesives and sealants used on the interior of the building shall comply with the requirements of South Coast Air Quality Management (SCAQMD) District Rule #1168. SCAQMD Rule#1168 sets volatile organic compound (VOC) limits for flooring adhesives applied on site to 50 grams per liter less water.

All of the following Burke Flooring Adhesives are in compliance with the requirements of SCAQMD Rule #1168. Specific VOC levels for each adhesive are as follows:

Burke Flooring BR-101 Cove Base Adhesive = Negligible (0 grams/liter)
Burke Flooring BR-710 One Part Urethane Adhesive = < 12 grams/liter
Burke Flooring BR-711 Rubber & Vinyl Tile & Tread Adhesive = Negligible (0 grams/liter)
Burke Flooring BR-715 Epoxy Nose Filler = < 12 grams/liter
Burke Flooring BR-721 Two-Part Epoxy Adhesive = < 12 grams/liter
Burke Flooring BR-725 Two-Part Urethane Adhesive = < 12 grams/liter

Note: Material Safety Data Sheets for all Burke Flooring Adhesive products are available at www.burkeflooring.com.