

MATERIAL SAFETY DATA SHEET

HELMICOL 3056 Part B

DATE: June 20, 2007

Burke BR-721 TWO PART EPOXY TILE ADHESIVE – PART B

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER: HELMITIN INC.

US: 11110 AIRPORT ROAD
OLIVE BRANCH, MS 38654
662-895-4565

CANADA: 99 SHORNCLIFFE ROAD
TORONTO, ONTARIO M8Z 5K7
416-239-3105

EMERGENCY PHONE:

800-424-9300 (CHEMTREC)

613-996-6666 (CANUTEC)

TRADE NAME AND SYNONYMS: HELMICOL 3056 Part B

CHEMICAL NAME AND SYNONYMS: Epoxy Resin Curative

CHEMICAL FAMILY: Polyamide/Polyamine

MOLECULAR FORMULA: Blend

PRODUCT DESCRIPTION: EPOXY CURATIVE; PART B

2. COMPOSITION/INFORMATION ON INGREDIENTS

MATERIAL	CAS #	% BY WT.	OSHA EXPOSURE GUIDELINES	
			TLV-TWA	PEL-STEL
POLYAMIDE	68410231	27 – 37%	Not Established	
POLYAMINE	Proprietary	4 – 12%	Not Established	
PHENOL	108-95-2	3 - 9%	5 PPM	5 PPM
TETRAETHYLENE PENTAMINE	112-57-2	3 - 9%	Not Established	
BUTYL BENZYL PHTHALATE	85-68-7	3 – 7%	5 Mg/M ³	5 Mg/M ³
TRIS (DIMETHYL AMINO METHYL) PHENOL	90-72-2	2 – 7%		

3. HAZARDOUS IDENTIFICATIONS

EMERGENCY OVERVIEW: Causes eye burns or irritation. Can cause severe respiratory irritation.. Can cause dermatitis. Corrosive.

POTENTIAL HEALTH EFFECTS:

EYE: May cause severe irritation. May damage or burn eyes.

SKIN: Prolonged exposure may cause skin irritation or burns. May cause drying or flaking of skin. Skin absorption of material may cause systemic toxicity.

CONTINUED ON NEXT PAGE

INGESTION: Ingestion may cause severe injury to intestinal tract, liver, kidneys, stomach, throat, lungs, mouth and mucous membranes. Harmful or fatal if swallowed. Do not ingest.

INHALATION: Overexposure may cause severe respiratory tract irritation. Prolonged overexposure may cause central nervous system depression with narcotic effects (headaches, dizziness). Keep exposure below OSHA exposure limits.

CHRONIC EFFECTS / CARCINOGENICITY (CANCER CAUSING):

- IARC : Not suspected as a human carcinogen
- OSHA : Not suspected as a human carcinogen
- NTP : Not suspected as a human carcinogen
- OTHER : None known

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.

SKIN: Wash with soap and water. Get medical attention if irritation develops or persists. Immediately remove contaminated clothing.

INGESTION: If swallowed, seek medical attention immediately.

INHALATION: Remove to fresh air. Restore breathing if necessary. Get medical attention. This material can cause lung damage.

DO NOT LEAVE VICTIM UNATTENDED.

5. FIRE FIGHTING MEASURES AND FIRE HAZARDS

OSHA CLASS: IIIB
FLASH POINT: >200° TAG CLOSED CUP
LOWER EXPLOSIVE LIMIT: Not Applicable

GENERAL HAZARD: May release flammable mixtures when temperatures are at or above the flash point. Toxic gases will form upon combustion. Closed containers may explode when exposed to extreme heat. Vapors are heavier than air and may travel a considerable distance.

FIRE FIGHTING EQUIPMENT: Respiratory and eye protection required for fire fighting personnel. Full protective equipment and a self-contained breathing apparatus (SCBA) should be used in all indoor fires and any large outdoor fires.

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide, carbon dioxide, smoke and fumes, hydrocarbon fragments, nitrogen oxides, amino compounds.

CONTINUED ON NEXT PAGE

6. ACCIDENTAL RELEASE MEASURES (SPILLS OR LEAKS)

Keep all sources of ignition and hot metal surfaces away from spill. Isolate the danger area and keep unauthorized personnel out. Stop spill if it can be done with minimal risk. Wear appropriate protective equipment including respirator protection as conditions warrant (see section 8). Prevent additional discharge of material. Notify the appropriate authorities immediately. Contain spilled liquid with sand, earth or other non-combustible inert absorbent material. Prevent run off from entering storm sewers, ditches or waterways. Transfer absorbed waste material into properly identified drums. Treat waste material with same precautions as the adhesive.

Do not use solvent or flammable liquid to help clean up an accidental release.

Release to the environment may be reportable under environmental regulations

7. HANDLING AND STORAGE

HANDLING: Open container slowly to relieve any pressure. Bond and ground all equipment when transferring from one vessel or container to another. This material can accumulate static charge by flow or agitation. Use spark proof tools and explosion proof equipment as directed by local fire codes. Do not enter confined spaces such as tanks without following proper entry procedures as described in OSHA regulations at 29 CFR 1910.146. Do not breathe vapors. The use of respiratory protection is recommended when airborne concentrations of vapor exceed exposure guidelines. Wash thoroughly after handling. Do not wear contaminated clothing or shoes. Wear appropriate protective gloves and clothing to prevent prolonged or repeated skin contact. Avoid contact with eyes.

“EMPTY” containers may contain liquid and vapor residue and may be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury or death. “EMPTY” drums should be completely drained, properly bunged, and promptly shipped to the supplier or a drum reconditioner. All containers should be disposed of in accordance with governmental regulations.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, smoke and fumes, hydrocarbon fragments, nitrogen oxides, amino compounds.

HAZARDOUS POLYMERIZATION: Will not occur.

STORAGE: Keep containers tightly closed. Use and store this material in cool, dry, well-ventilated area away from heat, direct sunlight, hot metal surfaces, and all sources of ignition. Post area “No smoking or open flames.” Store only in approved containers. Protect containers against physical damage. Indoor storage should meet OSHA standards and appropriate fire codes.

Wash with soap and water before eating, drinking, smoking or using toilet facilities.

Consult NFPA and OSHA codes.

CONTINUED ON NEXT PAGE

8. EXPOSURE CONTROLS, PERSONAL PROTECTION

RESPIRATORY PROTECTION: A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge may be used under conditions where airborne concentrations are expected to exceed exposure guidelines. Protection provided by air purifying respirators is limited. Refer to respirator manufacturer's selection guide for appropriate respirator for conditions encountered. If in doubt, seek the advice of an industrial hygienist or safety professional for appropriate air purifying respiratory equipment. Use positive pressure air supplied respirator if there is potential for an uncontrolled release, exposure levels are not known, or in any other circumstances where air purifying respirators may not provide adequate protection. Respiratory protection does not provide safety from flammable atmospheres. Do not enter concentrations of vapors at, near or above the Lower Flammable Limit (LFL). When respiratory protection is used, a respiratory protection program meeting OSHA regulations at 29 CFR 1910.134 must be followed.

SKIN PROTECTION: The use of gloves impermeable to the specific material handled is advised to prevent prolonged or repeated skin contact. Where splashing is likely to occur, aprons impermeable to the specific material may be worn. Refer to the glove and protective clothing manufacturer's selection guide for appropriate material.

EYE PROTECTION: Approved chemical splash goggles should be worn to safeguard against potential eye contact, irritation or injury. Where splashing is likely to occur, hard hats and face shields may be used to provide additional protection. Eye wash facilities should be available in the work area.

ENGINEERING CONTROLS: Provide sufficient mechanical ventilation to maintain exposure below TLV(S). The use of local exhaust ventilation is recommended. Provide mechanical ventilation of confined spaces. If current ventilation practices are not adequate to maintain airborne concentrations below the established exposure guidelines, additional ventilation or exhaust systems may be required.

9. PHYSICAL AND CHEMICAL PROPERTIES

ODOR AND APPEARANCE: Beige paste with amine odor

SPECIFIC GRAVITY: ~1.3 (68°F 20°C) pH: N/A

BOILING POINT: ~350 °F FREEZE POINT: <32 °F

APPROXIMATE VISCOSITY: Paste 75°F (24°C)

SOLUBILITY IN WATER: Slightly Soluble

% SOLIDS BY WEIGHT: >99 %

PERCENT VOLATILE (BY WEIGHT): <1%

VAPOUR PRESSURE (MM OF MERCURY): <1 mm Hg

VAPOUR DENSITY (AIR = 1): more dense

EVAPORATION RATE (BUTYL ACETATE = 1): slower

EVAPORATION RATE (ETHYL ETHER = 1): slower

CONTINUED ON NEXT PAGE

10. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Keep away from flames and spark producing equipment. Not dangerously unstable. Avoid build-up of static electricity.

INCOMPATIBLE MATERIALS: Strong oxidizing agents, strong reducing agents, acids, bases, or unstable chemicals, chloroform, peroxides, sulfur dichloride, strong alkalies, anhydrides, mercaptans, materials that react with amines.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, smoke and fumes, hydrocarbon fragments, nitrogen oxides, amino compounds.

HAZARDOUS POLYMERIZATION: Will not occur.

11. TOXICOLOGICAL INFORMATION

SKIN: DERMAL LD50 = Not available mg/kg

INGESTION: ORAL LD50 = Not available mg/kg

CHRONIC: Liver and kidney damage. may cause corneal opacity. may cause central nervous system depression causing headaches, nausea, dizziness.

CHRONIC/CARCINOGENICITY (CANCER CAUSING):

This product contains the following chemicals known to the state of California (Proposition 65) to cause cancer or reproductive toxicity:

None Known

OTHER:

None known

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Incinerate at an EPA approved facility or dispose of in accordance to all federal, state and local regulations.

Helmicol 3056B is a hazardous waste if discarded. (CFR., vol. 40, part 261, PGS. 51-114).

See section 2, page 1 of this MSDS for hazardous ingredients.

CONTINUED ON NEXT PAGE

PROPER WASTE DISPOSAL IS THE RESPONSIBILITY OF THE OWNER OF THE WASTE!

Call Helmitin Inc. for further information.

14. TRANSPORTATION INFORMATION

DOT: TDG:

PROPER SHIPPING NAME: Not Regulated

HAZARD CLASSIFICATION: _____

UN#: _____

PACKING GROUP: _____

All packaged material must be labeled in accordance with DOT and OSHA standards.

ERG (EMERGENCY RESPONSE GUIDE):

15. REGULATORY INFORMATION

OSHA: Hazardous material by definition of hazard communication standard (29 CFR 1910. 1200).

SECTION 313: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of Superfund Amendments And Reauthorization Act of 1986 and CFR part 372: _____
BUTYL BENZYL PHTHALATE, PHENOL

V.O.C.: <0.1 LBS/GAL (SCAQMD RULE 1168)
<12 G/L

HAZARD INDEX:

- 0: MINIMAL HAZARD 2: MODERATE HAZARD
- 1: SLIGHT HAZARD 3: SERIOUS HAZARD

HMIS RATINGS:

HEALTH: 2

REACTIVITY: 0

FLAMMABILITY: 1

PERSONAL PROTECTION: DEPENDS ON APPLICATION AND VENTILATION.

TSCA: Components of this product are listed on the TSCA inventory.

16. OTHER INFORMATION

Revision Number: 3

All employees or contractors, etc., who use this product must have access to this material safety data sheet.

PREPARED BY: Helmitin Inc Lab (MW)

17. DEFINITIONS

ASPIRATION HAZARD: The danger of drawing material into the lungs, leading to an inflammatory response that can be fatal.

CFR: Code of Federal Regulations. A collection of regulations established by law.

CARCINOGEN: A material that either causes cancer in humans, or is considered capable of causing cancer in humans.

COMBUSTIBLE: A term used to classify certain materials with low flash points that ignite easily. For OSHA it has a flash point >100°F but below 200°F.

D.O.T.: U.S. Dept. of Transportation

FLAMMABLE: A material that gives off vapors that readily ignite at room temperature. OSHA defines flammable as a material with a flash point <100°F.

FLASH POINT: The lowest point at which a liquid gives off sufficient vapor to form an ignitable mixture with air.

HAZARDOUS: Any substance or mixture of substances having properties capable of producing adverse effects on the health or safety of a human.

IARC: International agency for research on cancer

IRRITANT: A substance capable of causing an inflammatory effect on living tissue by chemical action at the site of contact.

LD50: Lethal Dose 50. The single dose of a substance that causes death of 50% of an animal population from exposure to the substance from any route other than inhalation.

L.E.L.: Lower Explosive Limit. The lowest concentration of vapor that burns or explodes when an ignition source is present at ambient temperatures.

L.F.L.: Lower Flammable Limit. Same as L.E.L.

MSHA: Mine Safety And Health Administration

N.A.: Not applicable or not available.

N.E.: Not established

N.F.P.A.: National Fire Protection Association

N.I.O.S.H.: National Institute Of Occupational Safety And Health.

N.T.P. National Toxicology Program.

O.S.H.A.: The Occupational Safety And Health Administration

P.E.L.-S.T.E.L.: Permissible Exposure Limit, Short Term Exposure Limit.

SYSTEMIC TOXICITY: Adverse effects induced by a substance which affects the body in a general manner rather than locally.

T.L.V.-T.W.A.: Threshold Limit Value, Time Weighted Average

T.S.C.A.: Toxic Substance Control Act

TOXIC: Any chemical or material that has evidence of an acute or chronic health hazard and is listed in the NIOSH REGISTRY OF TOXIC EFFECTS OF CHEMICAL SUBSTANCES.

V.O.C.: Volatile Organic Compound

Filename: burke_br_721_two_part_epoxy_tile_adhesive_part_b_3056b.doc
Directory: C:\All Data\Burke Ind\MSDS Files
Template: C:\Documents and Settings\User\Application
Data\Microsoft\Templates\Normal.dot
Title: MATERIAL SAFETY DATA SHEET
Subject:
Author: Valued Gateway 2000 Customer
Keywords:
Comments:
Creation Date: 5/16/2008 2:56 PM
Change Number: 4
Last Saved On: 2/12/2009 3:01 PM
Last Saved By: Dan Kelly
Total Editing Time: 0 Minutes
Last Printed On: 2/12/2009 3:03 PM
As of Last Complete Printing
Number of Pages: 8
Number of Words: 2,275 (approx.)
Number of Characters: 13,404 (approx.)